

ULTRASEAL BRUSH



**ULTRA
SEAL**
THE WATERPROOFING CHOICE



Weather
Resistant



Durable &
Flexible



UV
Stable

Ultraseal Brush is the polyol component of a two-component solvent-less, elastoplastic polyurethane system

Manufactured by NUI – Member of the RIGIFoam Group

ULTRASEAL BRUSH



Ultraseal Brush is the polyol component of a two-component solvent-less, elastoplastic polyurethane system formulated for high build brush application. When combined, the products react to form a hard, but tough compound, which exhibits the excellent resistance to:

- Corrosion ● Chemicals ● Abrasion ● Impact ● Weather ● Permeability

PROCESSING AND APPLICATION

Ultraseal Brush are supplied in pre-weighed containers in kit form. After combination of the two ingredients, which should preferably be below 25° C, sufficient mixing must be undertaken to produce a homogenous single colour compound without streaks. It is important to ensure that material adhering to the sides and bottom of the container is incorporated into the mix.

Application of the product must be undertaken within ± 12 minutes, timed from the beginning of the mixing of the two components. The viscosity will rise rapidly after 12 minutes, becoming unusable after 15 – 25 minutes (depending on ambient temperatures). **Ultraseal Brush** can be applied by squeegee, brush or roller.

The total recommended coating thickness is 1 – 3 mm where impact and abrasion are a consideration.

ADVANTAGES

The advantages of **Ultraseal Brush** waterproofing are that it is fast and easy to apply, it features a seamless finish, and offers durability as well as resistance to water, weather conditions, and many chemicals.

Common applications include roofs, balconies, terraces, kitchens, basements, patios and wet areas.

COLOURS



± 24 HRS



WEATHERABLE

± 24 HRS



TRAFFICABLE

± 10 YRS



LIFESPAN

APPLICATION METHODS



TOUCH
DRY



± 3 hours

FULL
CURE




24 hours

OVER-
COATING



3 - 12hours

AVERAGE
COVERAGE



$\pm 0,75$ m² / Kg
at 1mm thick

Manufactured by NUI – Member of the RIGIFoam Group

www.ultraseal.co.za
www.rigifoam.co.za
+27 (0)11 421 0313



DISAVOWAL: The customer acknowledges and understands that after delivery, the goods will have left the control of Rigifoam (Pty) Ltd, and that the customer will be responsible for the unpacking of and connection/installation of the goods. The customer acknowledges that it is his/her further responsibility to ensure that a fully qualified and competent person is used to install the goods to ensure their effective operation. Failure by the customer to ensure the installation of the goods, according to the written instructions of the manufacturer and/or supplier, by a fully qualified and competent person, may result in the failure of the goods, injury, loss or damages to the customer. Accordingly, and in this event, Rigifoam (Pty) Ltd accepts no responsibility for any loss or damages that might arise by reason of death or personal injury to any person engaged in the installation or use of the goods thereafter, subject to the provisions of the Consumer Protection Act 68 of 2008.